

3045072S H.264 Real-Time DVR in 1U casing - 4 Channel

Features:

- H.264 compression chip, cost-effective, DSP format
- Pentaplex operational mode : Recording, playback, remote viewing, back up, live viewing, simultaneously
- Support 4-ch playback simultaneously
- Support SATA Hard Disk, up to 1pcs
- Live view resolution / resource
NTSC : 720 x 480 @ 120fps
PAL : 704 x 576 @ 100fps
- Recording resolution / resource
Real time mode
NTSC : 360 x 240 @ 120fps
PAL : 352 x 288 @ 100fps
- 4-Ch video input and 1-Ch video output
- 4-Ch audio input and 1-Ch audio output
- 4 suits of alarm inputs and 3 suits of alarm outputs
- Supports USB mouse
- RS-485 port for Pan / Tilt / Zoom control
- Playback: Channel selectable by single touch button during playback
- Remote view through IE browser or free bundle multi-client software



Model: 3045072S

Specifications:

System			
Processor	High performance embedded microprocessor	Operating System	Embedded LINUX
Video			
Video Input	4 channel, BNC, 1.0Vp-p, 75	Video Output	1 channel TV output, BNC 1 channel VGA output
Video Standards	NTSC (525Lines, 60Hz) PAL (625Lines, 50Hz)	Video Compression	H.264
Video Resolution	NTSC : 720 x 480 @ 120fps PAL : 704 x 576 @ 100fps	Recording Resolution / Resource	NTSC : 360 x 240 @ 120fps PAL : 352 x 288 @ 100fps
Video Display Split	1, 4	Image Quality	1 ~ 6 level (level 6 is the best)
Tour Display	Support	Video Information	Camera title, time, video loss, motion detection, recording
Camera Adjustment	Adjust color according to different time period	Privacy Masking	Self-defined four-side zone for privacy masking for each camera
Audio			
Audio Compression	ADPCM	Audio Input	4 channel
Audio Output	1 channel		

talitor (Far East) Company Limited

6F.-6, No.646, Sec. 5, Chongsin Rd., Sanchong City, Taipei County 241, Taiwan

Tel : +886 2 8511 0020 Fax : +886 2 8511 0028

Email : sales@talitor.com.tw

Web site : www.talitor.com

3045072S H.264 Real-Time DVR in 1U casing - 4 Channel

Specifications:

Video Detection & Alarm			
Motion Detection	22 * 18 = 396 areas (PAL) 22 * 15 = 330 areas (NTSC)	Video Loss	Trigger recording, alarm
Alarm Input	4 channel	Relay Output	3 channel
Record, Playback & Backup			
Recording Mode	Manual, continuous, MD, alarm, schedule	Recording Priority	Manual>alarm>MD> continuous
Recording Interval	1 to 120 min. (default : 60min)	Playback	4 channel playback simultaneously
Search Mode	Time/Date, Alarm, MD	Backup Mode	Flash stick, USB HDD, USB CD-RW, USB DVD-RW, Network
Network			
Interface	RJ-45 port (10/100M)	Network Function	TCP/IP, DHCP
Remote operation	Monitor, PTZ control, playback, system setting, file download, log information		
Auxiliary Interface			
USB interface	2 ports	RS-232	PC communication
RS-485	Pan/Tilt/Zoom control		
Environment			
Power Supply	115V 60HZ / 230V 50Hz	Power Consumption	25W
Working Temperature	-10°C ~ +55 °C	Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa ~ 106kpa		

Package Contains

- DVR x 1
- Power adapter x 1
- Power cable x 1
- Ethernet cable x 1
- Remote control x 1
- USB mouse x 1
- Accessories x 1
- CD-ROM (included User manual, ASP software..) x 1

talitor (Far East) Company Limited

6F.-6, No.646, Sec. 5, Chongsin Rd., Sanchong City, Taipei County 241, Taiwan

Tel : +886 2 8511 0020 Fax : +886 2 8511 0028

Email : sales@talitor.com.tw

Web site : www.talitor.com