

3050121~3050123 IP Dome Camera

Features

- Compact Size
- Built in video server for direct networking applications
- Pan for 360° and tilt for 90° (75° when use vari-focus lens)
- Fast search speed of 300° per second
- M-JPEG compression with excellent video quality
- View position present, up to 20 spots
- Support IE browser for remote view
- Resolution options to accommodate bandwidth variation
- Easy to mount – Embedded or bracket mount
- Night vision capability (optional function)



Model : 3050121~3

Specifications

Scan/ Search	Navigation range	Pan 360° Tilt 90° 75° (vari-focus lens)
	Search speed	Programmable, up to 300° / sec
	View Position	Programmable, Max 20 positions
	Dwell time	Programmable, Max 255 seconds
Communication	Protocol	RS-485
Video Output	Format	NTSC or PAL (optional)
	Level	1.0 V (typical)
Power	Input	DC 12
Connectivity	Network	RJ-45 ethernet connector
	Video Output	RCA
	RS-485 communication	RJ-11 phone jack
	DC input jack	
Operation	Temperature	0 ~ 40℃
	Humidity	20 ~ 90% RHD
Storage	Temperature	-20℃~ 70℃
Certification	FCC, CE (pending)	

Optical System

	Standard	Day & Night
Model Number	3050121	3050123
Type of Sensor	1/3" CCD	1/3" CCD
CCD Resolution	380 lines	380 lines
Type of Lens	Fixed	Fixed
Light Sensitivity	1.0 lux	0.5 lux
Aperture Size	F 2.0	F 2.0
Iris Control	DC control	Electronics
IR Illumination	--	Yes

talitor (Far East) Company Limited

6F.-6, No.646, Sec. 5, Chongsin Rd., Sanchong City, Taipei County 241, Taiwan

Tel : +886 2 8511 0020 Fax : +886 2 8511 0028

Email : sales@talitor.com.tw

Web site : www.talitor.com